e.City Gold

Together towards a sustainable future. Your City, our Technology.





e.City Gold

SPECIFICATIONS



Powertrain	Siemens PM synchronous motor, 700V, 160 kW
	Transmission management Siemens ELFA
Power supply	Li-ion batteries (capacity individually configured)
	Plug-in charging CCS/Combo Fast Charging, 200 A
Axles and suspension	Independent front wheels suspension with antiroll bar
	Low portal rear axle with antiroll bar
	Pneumatic suspension, electronically controled (ECAS)
	Kneeling
	Manual rise and lowering of suspension high
	275/70 R22.5" tyres
Braking system	EBS3 (electronic braking system) with ABS, ASR (Acceleration slip regulation) and disk brakes
	Regenerative braking
Chassis	Ladder type chassis, welded construction, of high-strength steel
Body	Aluminium body panelling
	Aluminium side and roof structures
	Front and rear in glassfiber reinforced plastic (GFRP) with high-strenght steel structure
Lights	Full-LED interior and exterior lighting
Passengers area	Capacity up to 88 passengers (depending on configuration)
Doors	2 or 3 double-wing doors, electro-pneumatic drive
	Ramp on door 2 (manual or electric), optional on door 1
Windows	Panoramic windows in tempered safety glass, single glazing
	Laminated windscreen
	Driver's window with integrated resistance
Climatization	Electric HVAC system with air conditioning, roof mounted
	Independent driver's climatization
	Optional auxiliary heater (electric or biodiesel)
Driver's place	Instrument panel tiltable with steering column
	Configurable central display (TFT color display)
	Pneumatic driver's seat
	Heated exterior rearview mirrors, electrically adjustable
	Sunblind on windscreen, electric
Manufacturer reserves the right to change product specifications.	



